

1295 PAVEMENT FRICTION TESTER (PFT)

The Dynatest 1295 Pavement Friction Tester (PFT) measures the average locked wheel (skid) and peak (slip) friction characteristics on dry or self-wetted paved surfaces. It is designed for maintenance testing to evaluate the alteration of pavement friction resulting from traffic, aging and weathering. The PFT consists of a fully instrumented tow vehicle and test trailer and utilizes the Dynatest two-axis transducer to provide real-time vertical load and horizontal tractive force measurements.



COMPLIANCE WITH INDUSTRY STANDARDS

- ASTM E274 "Standard Test Method for Skid Resistance of Paved Surfaces Using a Full-Scale Tire"
- ASTM E1337 "Standard Test Method for Determining Longitudinal Peak Braking Coefficient of Paved Surfaces Using a Standard Reference Test Tire"
- ASTM E501 "Specification for Rib Tire for Pavement Skid Resistance Tests"
- ASTM E524 "Specification for Smooth Tire for Pavement Skid Resistance Tests"
- ASTM E556 "Calibrating a Wheel Force or Torque Transducer Using a Calibration Platform"

SYSTEM HARDWARE AND SOFTWARE FEATURES

- Two-axis transducer provides direct measurement of both horizontal traction force and vertical load on the test wheels
- Trailer equipped with a parallelogram suspension, non-resonant combination of coil springs with heavy duty air shocks and disc brakes
- Solid state electronics and instrumentation
- Simple trim system calibration
- Full system diagnostics of transducer, encoders, brakes, and water system
- Test headers, skid numbers, peak friction values, can be stored and optionally printed
- On-board computer calculates Skid Number (SN) and Peak Braking Coefficient (PBC) in real time and displays friction and speed traces for each test

AVAILABLE UPGRADE OPTIONS

- Dual side measurement and wetting
- Texture laser
- Differential GPS
- Right of Way camera



www.dynatest.com

Dynatest A/S, HQ
Tempovej 27-29
2750 Ballerup
Denmark

Dynatest US, Inc.
576 NE 23RD AVE
Gainesville, FL 32609
USA

 **Dynatest®**