

## 8082 HEAVY WEIGHT DEFLECTOMETER (HWD)

The Dynatest 8081 Heavy Weight Deflectometer (HWD) was designed with a high loading capability to meet the needs of airport and pavement agencies with extra thick, stiff pavement structures. The HWD can easily simulate and measure the load levels and response of large aircraft such as the Boeing 747/777 and the Airbus A380. The HWD can produce higher and wider range of load levels suitable to both the highway and airfield applications. Similar to the FWD, the HWD is designed to impart a load pulse to the pavement surface simulating the load produced by a rolling vehicle wheel. The load is produced by dropping a large weight on a set of rubber buffers on a bracket connected to a circular load plate. A load cell mounted on top of the plate measures the imparted load. Deflection sensors (geophones)

mounted radially in and from the center of the load plate measure the deformation of the pavement in response to the load.

The post processing software, Dynatest ELMOD (Evaluation of Layer Moduli and Overlay Design) can be used to backcalculate the pavement layer moduli based on the impact load and surface deflection basin. The results can effectively be used for the evaluation of pavement structural condition and overlay design based on empirical or mechanistic-empirical pavement design guides. The HWD data can also be used to calculate the degree of load transfer between adjacent concrete slabs, and to detect voids under slabs in rigid pavements.





## KEY FEATURES

- Nondestructive structural testing device
- Ideal for comprehensive testing for mechanistic-empirical analysis and design
- Very wide loading range—30–320 kN; suitable for testing a variety of paved and unpaved roadways, parking lots and airfield surfaces
- Allowing for simulation of new large aircraft such as A-380 and B-777
- Excellent repeatability
- Single person operation
- Quiet operation
- Accommodating up to 15 deflection sensors
- Up to 60 test points per hour
- AASHTO R32-11 calibration protocol compliant
- Passes TRL correlation trials

## STANDARD EQUIPMENT

- 4 segmented loading plate with swivel accommodates uneven or rutted pavement surfaces
- 7 or 9 deflection sensors (geophones)
- Air/Pavement Temperature Sensors
- Distance Measuring Instrument (DMI)

## AVAILABLE OPTIONS

- Global Positioning System (GPS)
- Camera system for plate location or Right of Way Imaging
- On board generator for standalone operation
- Trailer mounted light(s) or strobe(s)
- Rear or rear and transverse sensor extension bars
- Ground Penetrating Radar (GSSI or IDS)
- Spare parts kit
- Tool kit

## DATA COLLECTION SOFTWARE

- Intuitive and user-friendly software facilitates data collection in the field
- Supports multiple languages
- Stores the HWD data in Access (.mdb) databases for further process
- Generates the following legacy formats: .fwd, .f25, .PDDX
- Real-time plotting of the surface moduli along the test sections

## ELMOD SOFTWARE

### Evaluation of Layer Moduli and Overlay Design

- Dynatest's ELMOD software may be used for the analysis and design of flexible, rigid, and composite pavements
- Allows quick data reduction and analysis of HWD load/deflection measurements
- Capable of backcalculation of the layer moduli, for a typical drop sequence in less than a second
- Fast calculation of the seasonally adjusted moduli, residual life of the pavement, and required overlay thickness for a given service life
- For maintenance and rehabilitation (M&R), the LCCA (Life Cycle Cost Analysis) module allows the user to select the optimum M&R solution for a pavement section according to cost/benefit ratios
- For analysis of airfield pavements, the optional PCN module calculates PCN in accordance with the ACN/PCN method, as described in the ICAO and FAA design manuals. **NEW classification by the Civil Aviation Organization (ICAO) which will take effect in November 2024. The new ACR/PCR classification can be calculated alongside ACN/PCN in the ELMOD Software until fully applicable November 2024.**

[www.dynatest.com](http://www.dynatest.com)

**Dynatest A/S, HQ**  
Tempovej 27-29  
2750 Ballerup  
Denmark

**Dynatest US, Inc.**  
576 NE 23RD AVE  
Gainesville, FL 32609  
USA

 **Dynatest**<sup>®</sup>